



CLASS I DIVISION 2 SCREWDRIVERS

HAZLOC™
CLASS 1 DIVISION 2 RATED

"Quick Change"
1/4" Hex Shank Chuck

Torque Adjusting System

Auto-Stop
Fastening Function

L.E.D.
Indicator

Built-in L.E.D. Light

Anti-Slip
Dimpled Grip

Beeper Indicator

MAKSTAR®
CHARGING SYSTEM

2.0Ah
Nickel-Metal Hydride
12V
Ni-MH

Kit Includes:
2 Ea. (2.0Ah) Makstar®
Battery BH1220,
Makstar® Charger
DC18RA & Steel Case

CLASS I DIVISION 2 RATED

ADVANCED TECHNOLOGY



- UL listed for Class I Division 2 locations for maximum 50°C ambient
- Meets the NEC Article 513 Aircraft Hanger requirements for Class I Division 2 locations
- Tested to Mil Standard 810F, Method 511.4

SMART SYSTEM

AUTO BATTERY SHUT-OFF



- Shuts off the tool when battery capacity drops below 5%

Indication Lamp and Beeper

- Precision sensor indicates following conditions with light and/or beeping: sufficient fastening, insufficient fastening, low battery power, and battery too low to operate

REPETITIVE ACCURACY

TORQUE ACCURACY

- Torque accuracy of: +/- 10% with $C_m \geq 1.67$
- Automatically shuts-off tool when pre-set fastening torque is reached to ensure accuracy

PRECISE TORQUE CONTROL SCREWDRIVERS



BFH040FRAE



BFH040RAE



BFH090FRAE



BFH090RAE



BFH120FRAE

	BFH040FRAE	BFH040RAE	BFH090FRAE	BFH090RAE	BFH120FRAE
Voltage	12V	12V	12V	12V	12V
Capacities	1/4" Hex Shank	1/4" Hex Shank	1/4" Hex Shank	1/4" Hex Shank	1/4" Hex Shank
Max. Fastening Torque [Nm (in.lbs.)]	.8 - 4.5(7-40)	.8 - 4.5(7-40)	3.4 - 9.0(30-80)	3.4 - 9.0(30-80)	5.0 - 12.0(44-106)
No Load Speed (RPM)	400	400	400	400	400
LED Lamp	YES	NO	YES	NO	YES
LED Pass/Fail	YES	YES	YES	YES	YES
Audible Signal	YES	NO	YES	NO	YES
Length	7-15/32"	7-15/32"	7-15/32"	7-15/32"	7-15/32"
Height	10-15/32"	10-15/32"	10-15/32"	10-15/32"	10-15/32"
Width	2-13/16"	2-13/16"	2-13/16"	2-13/16"	2-13/16"
Weight	3.3 lbs.	3.3 lbs.	3.3 lbs.	3.3 lbs.	3.3 lbs.

MAKITA CORDLESS



14.4V Lithium-Ion Clutch Tools



Pistol Grip Screwdrivers

BFT022FZ	0.5 – 2 Nm	700 RPM
----------	------------	---------

BFT044FZ	1 – 4 Nm	950 RPM
----------	----------	---------

BFT084FZ	3 – 8 Nm	780 RPM
----------	----------	---------

BFT084FAZ	3 – 8 Nm	780 RPM
-----------	----------	---------

BFT126FZ	5 – 12 Nm	410 RPM
----------	-----------	---------

BFT126FAZ	5 – 12 Nm	410 RPM
-----------	-----------	---------

Low-Speed Pistol Grip Screwdrivers

BFT083FZ	3 – 8 Nm	80 RPM
----------	----------	--------

BFT083FAZ	3 – 8 Nm	80 RPM
-----------	----------	--------

BFT125FZ	5 – 12 Nm	150 RPM
----------	-----------	---------

BFT125FAZ	5 – 12 Nm	150 RPM
-----------	-----------	---------

Right Angle Nutrunners

BFL082FZ	2 – 8 Nm	700 RPM
----------	----------	---------

BFL082F5Z	2 – 8 Nm	700 RPM
-----------	----------	---------

BFL122FZ	5 – 12 Nm	410 RPM
----------	-----------	---------

BFL122F5Z	5 – 12 Nm	410 RPM
-----------	-----------	---------

BFL202FZ	8 – 20 Nm	220 RPM
----------	-----------	---------

BFL300FZ	16 – 30 Nm	400 RPM
----------	------------	---------

BFL300FAZ	16 – 30 Nm	400 RPM
-----------	------------	---------

BFL400FZ	25 – 40 Nm	260 RPM
----------	------------	---------

BFL400FAZ	25 – 40 Nm	260 RPM
-----------	------------	---------

*FAZ models have Low-Reaction nose piece.

*F5Z models have ¼" square drive.