

PT-4500 Cordless Blind Riveter for CHERRYMAX® & Blind Bolts

POWERFUL

VERSATILE

LIGHTWEIGHT

PRODUCTIVE



Specifications for PT-4500:

Pulling Force:	5,000 lbs.
Stroke:	0.984"
Dimensions:	11.5" H x 12" L x 3.25" W
Power Source:	2.1 Ah, 18vdc Li-Ion Battery
Charger Source:	Dual Voltage 120 volt, 60Hz 220 volt, 50 Hz
Charger Cycle Time:	40 Minutes
Optimal Operating Temp.	50 to 122°F
Housing Material:	Impact Resistant Glass Filled Nylon

The New, Higher Capacity PT-4500 Cordless Blind Riveter offers the sheet metal technician capability for installation of most all 1/4" diameter blind rivets while retaining all the features of the PT-4000 with respect to size, weight and versatility.

Powered by a slide on 18 VDC Li-Ion battery pack with fuel gage, the PT-4500 brushless motor drives a mechanical ball screw gear system that provides capability for the most demanding applications. With its rapid extended stroke capability the tool is comparable to most all air operated riveters, thereby optimizing cycle time between any blind rivet installation. Weighing less than 5 lbs with the standard nose assembly in place, sheet metal artisans will immediately find this riveter to offer the ultimate in overall performance and reliability.

The PT-4500 Kit includes the tool, 1 each battery pack and dual voltage battery charger.



PT-4500 (optional) Configurations

Standard Configuration

Nosepiece

F130-F
Nose Tube

F126-F
Jaw Holder

F122-A
2 pc Jaws

F3621
Jaw Follower

F3081
Spring



CherryMax® Pulling Head Configuration

Extended Straight
Pulling Head F1074

Right Angle Pulling Head
F1075

Offset Pulling Head
F1076

F187-1AR-4500
Sleeve

F187-3BCM
Adjustable Adapter
Shaft

CherryMax® & Pop® Rivets Configuration

*Note: Replace Jaw Follower F3621 with F3245 (see spare parts canister) when installing 1/4" dia. rivets. You may also use the F123 (3pc) jaws for 1/8" thru 1/4" diameter blind rivets. Use F142 Nosepiece.

F126-F
Jaw Holder

*F3621
Jaw Follower

F130-F
Nose Tube

F123
3 pc Jaws

F3081
Spring

*F3245
Jaw Follower

1/4" Rivets

MS90353/54 "U" & "S" Type Blind Bolt Configuration

Nosepiece

F130-F
Nose Tube

F123-A or
F123-B
BB Jaws

F128
BB Jaw Holder

F3081
Spring

F3245
Jaw Follower

Rivet Types:

Types of rivets installable with the PT-4500 include, but are not limited to, virtually all CherryMax®(M7885), Avdel®, or Cherry Monobolts®, Cherry Interlock®, Huck MagnaLok®, and Pop type rivets. The PT-4500 is also capable of installing both 5/32" and 3/16" Blind Bolts (MS90353/54-S/U) with the proper nosepieces (provided in the Mil-1 and MIL-2 kits).

Spare Parts:

F-4500A Battery Pack

18 v Battery Pack

F-3500A Battery Charger

Dual Voltage 110/220

Aerospace and Industrial Sheet Metal
●Applications●

